EcoMaster DELUXE EVO3

Drtič odpadu pro ty nejnáročnější



EAN: 8596220000040

397,08€

330.90 € bez DPH

It is suitable for larger households. It is a great choice for those who do not like to compromise and like to indulge in more luxury. From a technical point of view, this grinder brings perfection to every element down to the smallest detail.

Compared to cheaper models, it has the largest crushing chamber, the best possible soundproofing of the chamber and the engine. The crushing ring is higher, additionally equipped with a double row of perforations for faster and finer crushing. The longest warranty period is a matter of course.

This crusher is also suitable for less demanding catering operations with a frequency of 50-200 meals per day. For example, restaurants, pizzerias, cafes, kindergartens, smaller nursing homes, children's homes, pensions, confectioneries, snack bars, etc. Surface treatment of the throat - brushed matte stainless steel with the EcoMaster logo.

Welt Servis Ltd. holds products and spare parts in stock and provides warranty and post-warranty service and professional installations for households and catering establishments throughout the Czech Republic.

Grinder of the new generation - EcoMaster EVO3.

This crusher has already gone through its third series of innovations. It is equipped with a wider throat made of stainless steel. The packaging includes a stainless steel cap which, when the central button is pressed, transforms into a practical sieve. Compared to the previous generation, the crusher has even smaller dimensions, making it possible to place waste sorters in the sink cabinet. The power and maximum crushing speed have, of course, been preserved.

Antibacterial surface

The EcoMaster kitchen waste disposers are equipped with the antibacterial protection BIO GUARD. The material used to make the body of the disposer contains an antimicrobial agent that prevents the growth of a wide range of microorganisms and effectively eliminates bacteria that cause odour. Thanks to the BIO GUARD technology, the use of EcoMaster disposers is highly hygienic.

Warning! The packaging does not include a hose and a push button for the disposal unit. This is due to different connection options of the disposal unit (e.g. rocker switch on the wall) or it may be necessary to simply replace the disposal unit with a new one. Thank you for your understanding.

Parts of the packaging:

- · Assembly instructions
- Waste bend with additional inlet for overflow / dishwasher including flange and screws.
- Removable silicone cuff
- A plug made of high-quality stainless steel with a mesh function.

Parameters

Basic	parameters
Basic	parameters

Basic parameters	
Model:	EcoMaster DELUXE EVO3
Use:	Numerous households, small dining establishments (50-200 meals per day)
Warranty:	5 years
Product TARIC code:	85098000
Guarantee for use in gastronomic operations:	2 years
Technical parameters	
Mounting method - installation:	Hanging under the sink
Sink flange clamping system:	3-bold mount
Sink flange material:	All-metal (stainless steel)
Housing material - case:	ABS plastic
Surface finish - color:	White lacquer finish
Boot system:	Pressure air switch, button
Size of the chamber:	XL
Grinding segments:	Stainless steel, reinforced blades
Grinding ring:	114 circular holes, studs
Bearings:	Bronze, self-lubricating
Protective cushion:	Removable, silicone
Sink drain hole:	Ø 9cm (3.5 ")
Maximum sink thickness:	20 mm (at mounting point)
Dishwasher / washing machine connection, sink overflow:	Yes
Soundproofing:	Engine and grinding chamber cover + insulating filler
Possibility of running:	15 min / pause
Average water consumption:	10 l / running 3x a day approx
Waste pipe diameter:	min. 40 mm
Engine power (W):	550
Cuff material:	Silicone
Electric specifications	
Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Performance:	3/4 HP (550 W)
Current consumption:	2.25 A
Average el. consumption:	10 l / running 3x a day approx
Motor type:	Commutator DC
Engine speed:	2700 rpm
Torque:	1.8 Nm
Power cable:	CEE plug 7/7
Power cord length:	130 cm
Protective and security elements	
Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes
Interference filter:	Yes, it meets EMC-electromagnetic standards. compatibility
Electricity class protection: Dimensions, weight, packaging	I. (protective conductor)
Device dimensions:	393x194x194 mm (h / w / d)

Device weight:	5,6 kg
Packaging dimensions:	475x240x240 mm (h / w / d)
Weight including packaging (kg):	6.5
Width of the packaging:	24 cm
Height of the packaging:	47.5 cm
Depth of the packaging:	24 cm
Packing method:	Protective polybag, polystyrene cover, cardboard box















