

# EcoMaster HEAVY DUTY Plus

Drtič kuchyňského odpadu pro náročné



EAN: 8596220000033

**252,60 €**

210,50 € bez DPH

Food waste disposer is recommended for all households. It optimally combines all parameters and improvements typical for more luxurious models.

Compared to the cheaper STANDARD model, it has a larger and deeper grinding chamber, overall motor and chamber insulation, including insulation filling.

It also includes a waste bend with an inlet for potential connection of the sink overflow and an improved plug for filling the sink made of high-quality stainless steel with sealing, including a plastic longitudinal handle.

Surface treatment of the neck - polished matte stainless steel with the EcoMaster logo.

Welt Servis Ltd. holds products and spare parts in stock and provides warranty and post-warranty service and professional installations for households and catering establishments throughout the Czech Republic.

**Warning!** The packaging does not include a hose and a push button for the disposal unit. This is due to different connection options of the disposal unit (e.g. rocker switch on the wall) or it may be necessary to

*simply replace the disposal unit with a new one. Thank you for your understanding.*

**Parts of the packaging:**

- Assembly instructions
- Removable rubber cuff
- Waste bend with additional inlet for overflow / dishwasher including flange and screws.
- Plug made of high-quality stainless steel with seal including a plastic handle.

# Parameters

## Basic parameters

Model:	EcoMaster HEAVY DUTY Plus
Use:	Powerful model for demanding users
Warranty:	4 years
Product TARIC code:	85098000

## Technical parameters

Mounting method - installation:	Hanging under the sink
Sink flange clamping system:	EZ Mount
Sink flange material:	Plastic (Flanged Flange)
Housing material - case:	ABS plastic
Surface finish - color:	White lacquer finish
Boot system:	Pressure air switch, button
Size of the chamber:	L
Grinding segments:	Stainless steel, reinforced blades
Grinding ring:	36 arch holes, projections
Bearings:	Bronze, self-lubricating
Protective cushion:	Removable splash guard
Sink drain hole:	Ø 9cm (3.5 ")
Maximum sink thickness:	15 mm (at clamping point)
Dishwasher / washing machine connection, sink overflow:	Yes
Soundproofing:	Engine and grinding chamber cover + insulating filler
Average water consumption:	10 l / running 3x a day approx
Cuff material:	Rubber

## Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Performance:	3/4 HP (550 W)
Current consumption:	2.25 A
Motor type:	Commutator DC
Engine speed:	2700 rpm
Torque:	1.8 Nm
Power cable:	CEE plug 7/7
Power cord length:	140 cm
Engine power (W):	550

## Dimensions, weight, packaging

Device weight:	4,7 kg
Device dimensions:	413x167x167 mm (h/w/d)
Packaging dimensions:	475x230x230 mm (h/w/d)
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging:	23 cm
Height of the packaging:	47.5 cm
Depth of the packaging:	23 cm
Weight including packaging (kg):	5.6

## Protective and security elements

Resettable thermal fuse:	Yes, reset via fuse button
Short circuit protection:	Yes

Interference filter:	Yes, it meets EMC-electromagnetic standards. compatibility
Electricity class protection:	I. (protective conductor)

