

Jet Dryer II. JAKOST BOOSTER

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220009340x

126,84 €

105,70 € bez DPH

II. Jakost

Jet Dryer BOOSTER stříbrný - k dispozici jsou skladem 2 ks - ROZBALENO, mohou být mírné oděrky. Není v originál obalu, popř. může být obal poškozen

The drying power of the jet dryer is hidden in the compact Jet Dryer BOOSTER hot air dryer.

The construction is similar to the Jet Dryer STORM, but the difference lies in the drying nozzle, which is circular. Thanks to the metal cover with rounded corners, it is suitable for highly frequented operations.

Compared to using paper towels, operating a hot air dryer is significantly more economical. Additionally, you will save your cleaner's time.

Tryska in an interesting circular design.

The BOOSTER hand dryer is characterized by other chrome-plated round nozzle. Thanks to the powerful 550 W motor, hand drying is very fast.

Quick start

The construction of the heating element is designed in such a way that it quickly heats up to the operating temperature.

Antivandal metal design or ABS plastic.

If you choose Jet Dryer BOOSTER hand dryer with a metal body (brushed steel or white lacquer), you are guaranteed high mechanical resistance. You can place it in places where another dryer would not stand, such as pubs and nightclubs. BOOSTER is also available in a white ABS plastic variant.

High hygiene standard

The hand dryer automatically starts when hands are inserted. Your restroom visitors don't have to touch anything. The air coming out of the hand dryer is filtered through a dust filter.

The rounded design is also very easy to maintain, just wipe the dryer with a damp cloth and a little soap.

Dust filter

The BOOSTER dryer is equipped with a dust filter that protects the motor from clogging.

Parameters

Basic parameters

Model:	Jet Dryer BOOSTER
Use:	Suitable for all types of operations
Warranty:	2 years

Technical parameters

Mounting method - installation:	Wall
Noise - sound level:	75 dB
Surface finish - color:	White plastic / white lacquer / brushed stainless steel
Controls:	No
Status indication:	No
Boot system:	Automatic- infrared
Trigger distance:	15-20 cm
Warm air:	Automatically by ambient temperature / permanently ON
Air flow:	59 l / s
Air Speed:	50 m / s
UV sterilization:	No
Type:	hot air
Case material:	ABS plastic
Standard air filter:	Yes

Protective and security elements

Protection against excessive use:	Yes
Overcurrent protection, overheating and short-circuit protection:	Yes
Electricity class protection:	I. (protective conductor)
Degree of protection:	IP 23

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	1800 W
Heating element output:	1250 W
Motor power:	550 W
Motor type:	Serial AC commutator
Current consumption:	7.8 A
Standby mode:	<2 W
Power cable:	CEE plug 7/7
Power cord length:	90 cm

Dimensions, weight, packaging

Device dimensions:	320x221x190 mm (h/w/d)
Device weight:	ABS plastic 3.35 kg / metal 3.94 kg / stainless steel 3.68 kg
Packaging dimensions:	345x263x218 mm (v/š/h) 345x263x218 mm (h/w/d)
Weight including packaging (kg):	ABS plas 3.62 kg / metal 4.2 kg / stainless steel 3.95 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	26.3
Height of packaging (cm):	34.5

Depth of packaging (cm):

21.8

