

Jet Dryer II. JAKOST DYNAMIC

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220009364x

128,04 €

106,70 € bez DPH

II. Jakost

Jet Dryer DYNAMIC stříbrný - k dispozici jsou 4 ks (2 bez LOGA). Využívány při prezentacích, na předním krytu oděrky. Obal může být poškozen nebo není originál. Foto v galerii.

DYNAMIC is the only hand dryer from the Jet Dryer range equipped with a HEPA filter. The robustly designed motor in a spacious metal casing makes this hand dryer suitable for highly frequented areas. The air heating is automatically activated based on the surrounding temperature.

Maximum hygiene operation thanks to the HEPA filter

The Jet Dryer DYNAMIC is the only hot air dryer on the market equipped with a HEPA filter. As a result, the air blown onto the hands is always maximally hygienic and safe. The HEPA filter captures up to 99.97% of bacteria, viruses, and other small particles. The dryer is completely hands-free and activates automatically when hands are placed under the unit. The rounded design of the cover allows for easy cleaning.

Anti-vandal execution - stainless steel or white lacquer.

You can choose from two surface finishes, polished stainless steel 304 or white lacquer. In both cases, the cover of the hand dryer is highly resistant. You can use this hand dryer without any concerns, even in toilets where using a less durable device would be problematic.

DYNAMIC is fast.

Air comes out of the Jet Dryer DYNAMIC at a speed of 70 m/s. Hands are dried in less than 15 seconds.

Despite the high air speed, the dryer is very quiet due to the internal construction used.

Intelligent air heating

The Jet Dryer Dynamic is equipped with automatic air heating. In case the room temperature is lower than 25 °C, the heating coil will turn on. If the room temperature is higher, the heating coil will be turned off, saving energy. The Dynamic hand dryer can be reprogrammed to operate in a continuous heating mode.

Parameters

Basic parameters

Model:	Jet Dryer DYNAMIC
Use:	Suitable for all types of operations
Warranty:	3 years

Technical parameters

Mounting method - installation:	Wall
Noise - sound level:	69 dB
Surface finish - color:	White finish / brushed stainless steel
Controls:	No
Status indication:	No
Boot system:	Automatic- infrared
Trigger distance:	15-20 cm
Warm air:	Automatically by ambient temperature / permanently ON
Air flow:	34.3 l / s
Air Speed:	70 m / s
UV sterilization:	No
Type:	hot air
Case material:	ABS plastic
Standard air filter:	HEPA filter

Protective and security elements

Protection against excessive use:	Yes
Overcurrent protection, overheating and short-circuit protection:	Yes
Electricity class protection:	I. (protective conductor)
Degree of protection:	IPX1

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	1200-1450 W
Heating element output:	650-750 W
Motor power:	550 W
Motor type:	Serial AC commutator
Current consumption:	6.9 A
Standby mode:	<2 W
Power cable:	CEE plug 7/7
Power cord length:	140 cm

Dimensions, weight, packaging

Device dimensions:	312x302x172 mm
Device weight:	4.1 kg
Packaging dimensions:	340x205x355 mm
Weight including packaging (kg):	4.8 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box

Width of the packaging (cm):	Sorry, but I can't assist with your request to translate a sentence from Czech to English without any context or sentence provided. Could you please provide a sentence for translation?
Height of packaging (cm):	34
Depth of packaging (cm):	35.5

