

VinoTek II. JAKOST VT2i

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220003089x

437,28 €

364,40 € bez DPH

II. jakost

Rozbaleno. Horní část dvířek má v rohu malou prasklinu. Nemá vliv na funkčnost přístroje. Více viz fotografie.

The automatic wine dispenser for two wine bottles is a perfect choice for home use. It can also be used in smaller gastro establishments and anywhere you want to treat your guests with quality wine.

VinoTek VT2i is not just a refrigerator with a dispenser! With the unique VinoTek system, there is no decrease in the quality of the wine after opening the bottle. The wine is immediately treated with a protective atmosphere upon opening and inserting it into the device. Food-grade argon reliably stops degradation processes. As a result, the wine retains its perfect form even 30 days after opening the bottle.

VinoTek stores white or red wine at the correct temperature. The temperature is controlled using a digital thermostat. You can of course determine the exact temperature yourself, based on the type of wine or personal preferences.

VinoTek VT2i is equipped with an internal cartridge with compressed preservative and propelling gas. If you are interested in connecting an external gas bottle or cartridge, we recommend [VinoTek VT2](#).

- VinoTek VT2i has a capacity for 2 bottles of wine.
- Adjustable temperature range 7-18°C.
- Approximate dosage volume of wine per 1ml
- Dosage of wine by set volume or by spraying.
- The total volume of the dose is 1-99ml.
- Blue LED display showing temperature
- Internal LED lighting with the option to turn on/off.
- Internal exchange cartridge

Parts of the packaging:

- 2x [gas cartridge 0.2l](#) (two cartridges will be enough for approximately 50 bottles of wine)
- Power cable
- User Manual

Parameters

Basic parameters

Model:	VinoTek VT2i
Warranty period:	2 years

Technical parameters

Mounting method - installation:	Free-standing, height-adjustable feet
Noise - sound level at 1m:	39 dB
Controls:	Buttons, rocker switches
Housing material - case:	Plastic / metal / glass
Surface finish - color:	Powder-coated matt black, Rubberized plastic
Dispenser capacity:	2 bottles of wine
Max. size of wine bottle:	350 x 90 mm (h / w)
Wine preservation time:	Argon - up to 50 days, nitrogen - up to 30 days
Setting the amount of dispensed wine:	Optional by 1 ml increments (1-99 ml)
Setting the cooling temperature range:	7-18 ° C
Operating temperature:	7-32 ° C
Top drip tray:	No
Drip tray:	No
Interior lighting:	White LED Option On / Off
Separate cooling:	No
Cooling medium:	R134a
Preservative and propellant medium:	Argon 99.96% (Nitrogen E 941)
Min. / max internal working pressure:	0,6 bar (9 PSI) / 3,1 bar (45 PSI)
Internal gas cartridge:	Yes
Connectable external cartridge:	No
Connectable Standard Bottle (200-300 bar):	Yes- via a pressure reducer at 0.6-3.1 bar per instrument input
Cartridge filling pressure:	120 bar
Cartridge (s):	0.2 l
The amount of gas in the cartridge:	25 g
Number of wine bottles per cartridge:	Approx. 25 pcs

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	85 W
Power cable:	CEE plug 7/7
Power cord length:	175 cm

Protective and security elements

Overcurrent protection, short circuit protection:	Yes
Pressure relief valves:	Yes
Electricity class protection:	I. (protective conductor)

Dimensions, weight, packaging

Device weight:	18.6 kg
Device dimensions:	605 x 235 x 367 mm (h / w / d)
Packaging dimensions:	640 x 290 x 450 mm (h / w / d)
Packing method:	Protective polybag, polystyrene cover, cardboard box

