

VinoTek VT6 (3+3)

Automatický dávkovač vína na šest láhví. Dvě oddělené zóny na červené a bílé víno. Uchování vín až 30 dní po otevření.



EAN: 8596220003140

1 942,80 €

1 619,00 € bez DPH

The automatic wine dispenser VinoTek VT6 has two separate cooling chambers for red and white wine. The total capacity of the dispenser is 6 bottles of wine, which makes it suitable for medium-sized gastronomic establishments and wine enthusiasts' households.

The VinoTek system is not like ordinary wine fridges. The protective argon atmosphere prevents unwanted oxidation of the wine for up to thirty days after opening the bottle. You no longer have to offer quality wine only in full bottles. Provide hesitant guests with a tasting or serve wine "by the glass". By pressing a button, you dispense wine in a pre-selected volume. The approximate size of one wine serving can be set in the range of 0-99ml with an accuracy of 1ml. Thanks to this, VinoTek helps minimize losses. Each cooling chamber is equipped with its own thermostat and a display showing the temperature. This way, you can be sure that you are serving wine at the right temperature. The interior of VinoTek has optional lighting, making the presented wine clearly visible. The automatic dispenser contains an internal gas cartridge with a volume of 0.45l. This volume is sufficient for approximately 55 bottles of wine. VinoTek is equipped with an external input for connecting a second gas cartridge. It is also possible to connect a large pressure bottle with argon through the external input using a reducing valve.

- Capacity of the dispenser: 6 bottles of wine
- Adjustable temperature range 7-18 °C
- Approximate dosage volume of wine per 1ml
- Dosage of wine by set volume or by spraying.
- Blue LED display showing the temperature.
- Internal LED lighting with the option to turn on/off.
- Internal gas cartridge

- Entry to external gas cartridge
- The possibility of connecting a standard pressure gas cylinder.

Parts of the packaging:

- 2x [gas cartridge 0.45l](#) (two cartridges are enough for approximately 110 bottles of wine)
- External cartridge connection kit (hose, control valve).
- Top dropper
- User Manual

Parameters

Basic parameters

Model:	VinoTek VT6
Warranty period:	2 years

Technical parameters

Mounting method - installation:	Free-standing, height-adjustable feet
Noise - sound level at 1m:	39 dB
Controls:	Buttons, rocker switches
Housing material - case:	Plastic / metal / glass
Surface finish - color:	Powder-coated matt black, Rubberized plastic
Dispenser capacity:	6 bottles of wine
Max. size of wine bottle:	350 x 90 mm (h / w)
Wine preservation time:	Argon - up to 50 days, nitrogen - up to 30 days
Setting the amount of dispensed wine:	Optional by 1 ml increments (1-99 ml)
Setting the cooling temperature range:	7-18 ° C
Operating temperature:	7-32 ° C
Top drip tray:	Yes
Drip tray:	No
Interior lighting:	White LED optional
Separate cooling:	Yes
Preservative and propellant medium:	Argon 99.96% (Nitrogen E 941)
Min. / max internal working pressure:	0,6 bar (9 PSI) / 3,1 bar (45 PSI)
Internal gas cartridge:	Yes
Connectable external cartridge:	Yes
Connectable Standard Bottle (200-300 bar):	Yes- via a pressure reducer at 0.6-3.1 bar per instrument input
Cartridge filling pressure:	120 bar
Cartridge (s):	0.45 l
The amount of gas in the cartridge:	62 g
Number of wine bottles per cartridge:	Approx. 55 pcs

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	105 W
Power cord length:	150 cm

Protective and security elements

Overcurrent protection, short circuit protection:	Yes
Pressure relief valves:	Yes
Electricity class protection:	I. (protective conductor)

Dimensions, weight, packaging

Device weight:	46.7 kg
Device dimensions:	625 x 675 x 450 mm (h / w / d)
Packaging dimensions:	650 x 540 x 730 mm (h / w / d)
Packing method:	Protective polybag, polystyrene cover, cardboard box

